



MAX777

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
315/80R22.5	157/154T	70	73	9.00	4075/3750	850/900
12.00R24	160/157K	70	73.5	8.50	4500/4075	900/950



MAX586

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
12.00R24	160/157K	70	14.5	8.50	4300/4075	900/900



MAX608

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
11R22.5	146/148L	16	77	8.75	3000/2775	830/830
12R22.5	152/149M	18	73	9.00	3550/3250	950/950
205/80R22.5	152/149L	18	73	9.00	3550/3250	850/850
315/80R22.5	157/154L	23	78	9.00	4000/3750	850/850



MAX737

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
12R22.5	152/149M	18	77	9.00	3550/3250	950/950
205/80R22.5	152/149L	18	70	9.00	3550/3250	850/850
315/80R22.5	157/154L	20	77	9.00	4000/3750	850/850



MAX78

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
7.00R16LT	118/114L	14	32.5	6.50	1370/1080	770/770
7.50R16LT	122/119L	14	33	6.00	1600/1400	770/770
8.25R16LT	128/124K	16	32.5	6.50H	1800/1600	770/770
9.00R20	144/146L	16	33.5	7.00	2400/2100	900/900
10.00R20	149/146K	16	33.5	7.50	3200/3000	950/950
11.00R20	152/149K	18	35.5	8.00	3500/3250	950/950
12.00R20	156/153K	20	37.5	8.50	4000/3650	900/900
12.00R24	160/153K	20	36	8.50	4500/4025	900/900
11R22.5	146/148L	16	76	8.75	3000/2775	830/830
12R22.5	152/149M	18	75	9.00	3500/3250	900/900
315/80R22.5	157/154L	20	74.5	9.00	4000/3750	850/850



MAX580

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
315/80R22.5	156/150M	20	16	8.50	4000/3750	850/850
12.00R24	160/157K	20	16	8.50	4500/4025	900/900



MAX607

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
205/80R22.5	152/149L	18	6	9.00	3500/3250	850/850



MAX613

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
205/80R22.5	160K	20	14.5	11.75	4500	380



MAX619

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
385/65R22.5	160K	23	6	11.75	9100	380



MAX768

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
11R22.5	146/143L	16	22	8.25	3000/2725	830/830
205/80R22.5	152/149L	18	21	9.00	3500/3225	900/900
315/80R22.5	157/154L	20	21.5	9.00	4000/3750	850/850



MAX903

Size	LSR	PR	Tread Depth (mm)	Standard Rim	Max Load S3 (mm)	Pressure S300kPa
205/80R22.5	152/149L	18	24	9.00	3500/3250	840/840